

## Digger

### DR19



#### SPECIFICATIONS

| ITEM                  | U.S.A.                      | METRIC                  |
|-----------------------|-----------------------------|-------------------------|
| Capacity              | 3 1/4 in Shank x 7/8 in Hex | 82 mm Shank x 22 mm Hex |
| Weight                | 24 lb                       | 10.9 kg                 |
| Length                | 20 in                       | 50.8 cm                 |
| Width                 | 3 in                        | 76 mm                   |
| Pressure              | 1500-2000 psi               | 105-140 bar             |
| Flow Range            | 7-9 gpm                     | 26-34 lpm               |
| Optimum Flow          | 8 gpm                       | 30 lpm                  |
| Porting               | 6 SAE O-Ring                |                         |
| Hose Whips            | Yes                         |                         |
| Connect Size and Type | 3/8 in Male Pipe Hose End   |                         |

#### Features and Benefits

Stanley's **DR19** digger is compact and easy to handle in a trench. Its high blow frequency and power make short work of heavy clay and other material such as light shale.

The "D" handle as well as the tool holder end of the **DR19** are covered in a heat and shock insulating material for operator comfort.

## ACCESSORIES

### PART NO. DESCRIPTION

|       |  |
|-------|--|
| 02328 | Clay Spade 16 in/40.6 cm (U/C)*  |
| 02330 | 3 in/76 mm Chisel, 14 in/35.6 cm U/C*                                  |
| 02339 | 1 in/25 mm Chisel, 14 in/35.6 cm U/C*                                  |
| 02340 | Digging Chisel 3 x 10 in/7.6 x 2.54 cm Blade by 17 1/4 in/43.8 cm U/C* |
| 02341 | Asphalt Cutters, 5 in/12.7 cm Blade x 11 in/27.9 cm U/C*               |
| 04401 | Moil Point, 18 in/45.7 cm U/C*   |
| 04402 | 3 in/76 mm Chisel 18 in/45.7 cm U/C*                                   |
| 04403 | Concrete Buster, 14 in/35.6 cm U/C*                                    |
| 04901 | Moil Point, 14 in/35.6 cm U/C*   |

*\*U/C Denotes Under Collar*

## ORDERING INFORMATION

| PART NO. | SYSTEM      |
|----------|-------------|
| DR19111  | Open Center |

## WARRANTY

Stanley Hydraulic Tools and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.

All Stanley Hydraulic Tools, Parts, Accessories and allied equipment are subject to design improvements, specification and price changes at any time without notice and with no obligation to units already sold. Weights, dimensions and operating specifications listed herein are subject to change without notice. Where specifications are critical to your application, please consult Stanley Hydraulic Tools.

Call the Stanley Hydraulic Tools dealer nearest you...

**Stanley  
Hydraulic Tools**

**STANLEY**<sup>®</sup>

Steffen Inc  
623 W 7th Street  
Sioux City, IA 51103  
Toll Free: 800-382-3599  
Fax: 712-279-8070  
Email: stanley-sales@steffeninc.com